



***fib* Symposium2025**

Antibes - France

Concrete Structures :
extend lifespan, limit impacts

16-18 June, 2025



Experimental investigations to identify challenges in design of prefabricated concrete structures for disassembly and reuse

Ramon Hingorani (SINTEF Community, Norway)

and


Tore Myrland Jensen (SINTEF Community), Petra Rüther (SINTEF Community) , Vegard Ulme (Spenncon)

Reuse of prefabricated concrete components

- Reuse of prefab. components as strategy to mitigate environmental impact of concrete
 - Standard prefab. systems were not conceived for reuse
- Specific need for purpose-designed connections for disassembly




www.spenncon.no



www.spenncon.no

Motivation and objective


- Dry connection solutions often proposed as Dfd solutions: e.g. bolted joints
- Maintaining classical wet joints solutions relying on grouting concrete ensures:
 - adequate force transfer
 - constructability with regard to construction tolerances
 - Minimisation of adaptation costs
- **Objective:** Propose a Dfd solution for hollow core slabs (HCS) with wet joints and validate in full-scale mock-up




Figur 1 Dagens utførelse av fugebetong (foto: Vegard Alme Ulstein, Spenncon)

Function and design of longitudinal joints between HCS

- Primary function: Ensure structural force transfer and continuity through diaphragm action.
 - Design usually governed by horizontal shear capacity
 - Contribution from adhesion and friction forces
 - Grouted joints in precast floors are typically assumed to crack in service due to restraint forces.
- Shear resistance is assumed to rely on friction only
- Normal stress and reinforcement across joint.



Betongelementboken, 2016



Betongelementboken, 2016

Adhesion and Grout Removal: Prior experiences



- Despite assumption of cracked joints in design, adhesion forces between grout and HCS surfaces can be significant
 - Complicates disassembly
 - Increases time, cost, and risk of damage
- Example: Volda (Norway) swimming hall slab (2023)
 - ~15 min/m with chisel hammer to remove standard grout
- Adhesion increases with improved execution quality
 - Today: flowable concretes, pre-wetting, better curing & frost protection
- **Adhesion-lowering agents as solution**



Figur 3 Fjerning av fugestøp fra utsagede hulldekker fra Volda Symjehall, 2023 (foto: Vegard Alme Ulstein, Spenncon)



Mock-up description

- Planned and executed by Spenncon A.S. (Hønefoss, Norway)
- Hollow-core slabs (HCS) spanning two bays
- Supported by rectangular beam (1), inverted T-beam (ITB) (2), and a wall with nib (3)
- Vertical loads → transferred to columns + walls (axes 3 and A)
- Horizontal loads → resisted by diaphragm action and moment-resisting columns (1C, 2C)



HCS Support Connections and Detailing

- Rebars in longitudinal joints between HCS crossing connection II to ITB for continuity
- Threaded rods embedded in slots in connection III transfer force to wall
- Steel plates welded across end joints of the HCS to tie components together






Joint between HCS and ITB
(connection II)




Joint between HCS and wall
nib (connection III)

Disassembly considerations

- Cutting required through grout, rebars and threaded rods
- Threaded rods cut → new slot in HCS needed for reuse
- Existing sleeves in wall can be reused unless geometry misaligns
- 80 mm foam strip on top of HCS support prevents adhesion and damage during cutting
- **Adhesion-reducing agents**



Joint between HCS and wall nib
(connection III)



Joint between HCS and ITB
(connection II)



Adhesion-Reducing Products

- Seven products by Master Builders Solutions tested, based on prior laboratory study
- Application areas:
 - Longitudinal HCS side surfaces
 - Contact surfaces on supporting walls, and the ITB
 - Untreated reference zones for comparison
- Application process
 - Performed by Master Builders under open roof and dry weather
 - Low-viscosity liquids applied with pressure sprayers
 - Two thin layers on dry concrete
 - Drying time: ~15 minutes before 5-day storage prior to assembly



Application of the adhesion-reducing products on lateral surfaces of HCS.



Application on lateral surfaces of ITB.

Mock-up assembly

- Assembly took place August 2024
 - Two workers with assistance from a mobile crane
- Joint grouting with C30 concrete
 - Standard for summer joint casting in Norway
 - Weather: Humid conditions — no pre-watering applied




Grouting of end joints



Finished slab


Placing of a HCS with the mobile crane



Foam strip on top of wall nib supporting the HCS in axis C before grouting .

Disassembly of HCS

- > 4 weeks after assembly
- HCS removal sequence
 - Saw cutting of HCS end joints to wall nibs and ITB
 - HCS lifted with crane using embedded anchors
 - Shortened lifting chains to induce bending stress and hence controlled cracking in the nearest longitudinal joint
- Challenge and solution
 - Sometimes, unintended first cracking occurred at joint between the adjacent pair of HCS → damage risk
 - Shallow saw cuts + wedges + sledgehammer hits to induce cracking at intended joints



Reconditioning of HCS and adjacent members

- Removal of residual grouting concrete from HCS long and short sides, ITB web, Wall nib
- Performance of adhesion-reducing products:
 - Treated HCS long sides: Easy removal, 60–85 sec/m. Large sheets detached cleanly
 - Untreated areas: Difficult removal, 200–350 sec/m. Very labor-intensive, especially at short ends
 - One product showed notably higher adhesion; others performed similarly
 - Grout on beam side edges detached easily, regardless of adhesion-lowering agents
 - Grout on the wall above nib was only easy to remove where treatment was applied



Removal of concrete from longitudinal side of HCS, where adhesion-reducing products were applied






Removal from a reference area at the short end of the HCS

Lessons and envisaged improvements – Longitudinal joints

- Traditionally, adhesion neglected in HCS joint design
- Tests evidenced significant adhesion forces
- Adhesion-lowering products effective in cleaning phase
- Observed uncontrolled cracking during disassembly
- Reliability-based joint design to crack at predictable locations:


$$\sigma_{max}(F_{max}, \Delta, gH_{CS}) \geq \sigma_{R,adh}(p_{ft})$$

- Same principle for disassembly relying on uplift force:




Lessons and envisaged improvements – Longitudinal joints

- Further optimisation of adhesion-lowering agents
- Tests to ensure these agents do not imply friction loss:
 - Shear-off tests to study roughness/interlock effects.
 - Consider surface indents to improve friction capacity
- Reducing adhesion by lower grouting concrete strength is questionable strategy due to several reasons, e.g.
 - Requirements to frost protection (min C30/C35 in Norway).
 - Use same concrete for adjacent connections, such as e.g. floor-wall joints → low-strength mortars unsuitable.
 - Concrete tensile strength is crucial for anchoring reinforcement in longitudinal joints and HCS slots.



Fib bulletin, 43

Fig. 8-65: Slab with undulated sinusoidal edge according to tests by Menegotto (1994)



Vertical force transfer across wall-HCS joint in a multistorey building

Lessons and envisaged improvements – End connections

- Adhesion behaviour characterised by surface type
 - Free surfaces (not cast against formwork), e.g., wall above nib, require adhesion-reducing agents
 - Classified as “smooth” or “rough” per prEN 1992-1-1
 - Formwork-cast surfaces, e.g., ITB side edge, do not require such agents
 - Classified as “very smooth” per prEN 1992-1-1
 - Adhesion-reducing agents could also be applied to short ends of HCS, but risk of overspray into slits
- Saw cutting at interface between HCS and grout is preferred option



Conclusions

- Contrary to common belief, wet joints (grouted) can be suitable for reuse
- Adhesion forces in HCS joints can significantly resist disassembly and cleaning.
- Adhesion-reducing agents provide a viable and cost-effective solution to this problem
 - Preserve the benefits of wet joints (e.g. force transfer, diaphragm action, tolerances).
 - Outperforms strategy based on low-strength mortars, which face practical limitations.
 - Recommended for “smooth” or “rough” surfaces per prEN 1992-1-1.
- Induced tensile stress (via crane/jack) enables joint separation without prior grout removal.
- Further joint design optimization potential has been identified

Acknowledgements

Special thanks to Vegard Ulme (Spenncon) who is the main developer of this study.

The study received financial support from the **Research Council of Norway** via project no 327777 **SirkBygg: Sirkulære nybygg - Design og bygging for demontering og ombruk.**

Project owner: Skanska Norway (www.skanska.no).

Project partners: Spenncon A.S., Contiga (Heidelberg Materials), SINTEF Community